









DAY AND NIGHT SIGNAL

WesCom Signal and Rescue Germany GmbH

Chemwatch: 65-6265 Version No: 4.1.1.1

Safety Data Sheet (Conforms to Regulation (EU) No 2015/830)

Issue Date: 19/09/2016 Print Date: 19/10/2017 L.REACH.GBR.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1. Product Identifier

Product name	DAY AND NIGHT SIGNAL			
Synonyms	et Day and Night Signal, ArtNo. 9131500, Pains Wessex Day and Night MK8, Item No: 9559700			
Proper shipping name	SIGNAL DEVICES, HAND			
Other means of identification	Not Available			

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Use according to manufacturer's directions. Sea distress signal. Produces orange smoke and red flare. Housed in a rugged, corrosion water resistant case. For Day or Night use - only when rescue services are sighted.
Uses advised against	Not Applicable

1.3. Details of the supplier of the safety data sheet

	•	
Registered company name	WesCom Signal and Rescue Germany GmbH	
Address	Vieländer Weg 147 Bremerhaven 27574 Germany	
Telephone	+49 471 3930	
Fax	+49 471 3932 10	
Website	www.wescomsignal.com	
Email	info@wescomsignal.com	

1.4. Emergency telephone number

Association / Organisation	Consultant Lutz Harder GmbH		
Emergency telephone numbers	+49 178 433 7434		
Other emergency telephone numbers	Not Available		

SECTION 2 HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008 [CLP] [1]	H204 - Explosive Division 1.4
Legend:	1. Classified by Chemwatch; 2. Classification drawn from EC Directive 67/548/EEC - Annex I; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

2.2. Label elements

Hazard pictogram(s)



SIGNAL WORD	WARN
-------------	------

Hazard statement(s)

H204 Fire or projection hazard.

Precautionary statement(s) Prevention

• • • • • • • • • • • • • • • • • • • •		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P250	Do not subject to grinding/shock/sources of friction.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	

Page 2 of 13

Issue Date: 19/09/2016 Print Date: 19/10/2017

DAY AND NIGHT SIGNAL

P240 Ground/bond container and receiving equipment.

Precautionary statement(s) Response

P370+P380	In case of fire: Evacuate area.	
P372	Explosion risk in case of fire.	
P374	Fight fire with normal precautions from a reasonable distance.	
P373	DO NOT fight fire when fire reaches explosives.	

Precautionary statement(s) Storage

P401	Store according to local regulations for explosives.

Precautionary statement(s) Disposal

P501	Dispose of contents/container in accordance with local regulations.
POUL	Dispose of contents/container in accordance with local regulations

REACh - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.1.Substances

See 'Composition on ingredients' in Section 3.2

3 2 Mixtures

3.2.Mixtures			
1.CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP]
		device contains	
		lighter composition, delay composition and ignition composition	
		polytechnic materials of;	
1.7757-79-1 2.231-818-8 3.Not Available 4.01-2119488224-35- XXXX 01-2120104950-66-XXXX	30-60	potassium nitrate	Oxidizing Solid Category 3, Acute Toxicity (Oral) Category 4, Eye Irritation Category 2; H272, H302, H319 [1]
1.7439-95-4 2.231-104-6 3.012-001-00-3 012-002-00-9 4.01-2119537203-49- XXXX 01-2119940954-29- XXXX 01-2120113187-64-XXXX	30-60	magnesium	Flammable Solid Category 1, Emit Flammable Gases with Water Category 2; H228, H261 [1]
1.10042-76-9 2.233-131-9 3.Not Available 4.01-2119615605-42- XXXX 01-2120105844-60-XXXX	30-60	strontium nitrate	Oxidizing Solid Category 3, Skin Corrosion/Irritation Category 2, Eye Irritation Category 2, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation); H272, H315, H319, H335 [1]
1.10022-31-8 2.233-020-5 3.056-002-00-7 4.01-2119986880-22-XXXX	30-60	barium nitrate	Acute Toxicity (Inhalation) Category 4, Acute Toxicity (Oral) Category 4; H332, H302 [3]
1.7429-90-5 2.231-072-3 3.013-001-00-6 013-002-00-1 4.01-2119529243-45-XXXX	5-10	aluminium	Emit Flammable Gases with Water Category 3, Pyrophoric Solid Category 1; H261, H250 [3]
1.7778-74-7 2.231-912-9 3.017-008-00-5 4.01-2120021000-89-XXXX	1-5	potassium perchlorate	Oxidizing Solid Category 1, Acute Toxicity (Oral) Category 4; H271, H302 [3]
1.7704-34-9. 2.231-722-6 3.016-094-00-1 4.01-2119487295-27- XXXX 01-2119422098-42-XXXX	5-10	<u>sulfur</u>	Flammable Solid Category 2, Skin Corrosion/Irritation Category 2, Eye Irritation Category 2; H228, H315, H319 [1]
		smoke composition of;	
Not Available Not Available Not Available Not Available Not Available	30-60	dihydroxy anthrachinon	Not Applicable
Not Available Not Available Not Available Not Available Not Available	10-30	milk sugar	Not Applicable

Chemwatch: 65-6265 Issue Date: 19/09/2016 Page 3 of 13 Version No: 4.1.1.1 Print Date: 19/10/2017

DAY AND NIGHT SIGNAL

1.3811-04-9 2.223-289-7 3.017-004-00-3 4.01-2119494917-18-XXXX	10-30	potassium chlorate	Oxidizing Solid Category 1, Acute Toxicity (Inhalation) Category 4, Acute Toxicity (Oral) Category 4, Chronic Aquatic Hazard Category 2; H271, H332, H302, H411 [3]
Legend:	Legend: 1. Classified by Chernwatch; 2. Classification drawn from EC Directive 67/548/EEC - Annex I; 3. Classification drawn from EC Directive 1272/2008 - Annex VI 4. Classification drawn from C&L		

SECTION 4 FIRST AID MEASURES

4.1. Description of first aid measures

Eye Contact	If this product comes in contact with eyes: • Wash out immediately with water. • If irritation continues, seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Filush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay.
Ingestion	 Not considered a normal route of entry. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

5.1. Extinguishing media

DANGER: Deliver media remotely.

- For minor fires: Flooding quantities only.
 For large fires: Do not attempt to extinguish.

|Apply by mechanical means only.

5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contact with other chemicals.
5.3. Advice for firefighters	
Fire Fighting	WARNING: EXPLOSIVE MATERIALS / ARTICLES PRESENT! Evacuate all personnel and move upwind. Prevent re-entry. Alert Fire Brigade and tell them location and nature of hazard. May detonate and burning material may be propelled from fire. Wear full-body protective clothing with breathing apparatus. Prevent, by any means available, spillage and fire effluent from entering drains and water courses. Fight fire from safe distances and from protected locations. Use flooding quantities of water. DO NOT approach containers or packages suspected to be hot. Cool any exposed containers not involved in fire from a protected location. Equipment should be thoroughly decontaminated after use. Slight hazard when exposed to heat, flame and oxidisers.
Fire/Explosion Hazard	Division 1.4 Substances, mixtures and articles which present no significant hazard: substances, mixtures and articles which present only a small hazard in the event of ignition or initiation. The effects are largely confined to the package and no projection of fragments of appreciable size or range is to be expected. An external fire shall not cause virtually instantaneous explosion of almost the entire contents of the package. Compatibility Group G explosives are pyrotechnic substances, or article containing a pyrotechnic substances, or article containing both an explosive substance and an illuminating, incendiary, tear- or smoke-producing substance (other than a water-activated article or one containing white phosphorus, phosphides, a pyrophoric substance, a flammable liquid or gel, or hypergolic liquids). Combustible. Will burn if ignited. Combustion products include: , carbon monoxide (CO) , carbon dioxide (CO2) , other pyrolysis products typical of burning organic material.

Chemwatch: 65-6265 Page **4** of **13** Version No: 4.1.1.1

DAY AND NIGHT SIGNAL

Issue Date: 19/09/2016 Print Date: 19/10/2017

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

Minor Spills	WARNING!: EXPLOSIVE. BLAST and/or PROJECTION and/or FIRE HAZARD Clean up all spills immediately. Avoid inhalation of the material and avoid contact with eyes and skin. Wear impervious gloves and safety glasses. Remove all ignition sources. Use spark-free tools when handling. Sweep into non-sparking containers or barrels and moisten with water. Place spilled material in clean, sealable, labelled container for disposal. Flush area with large amounts of water.
Major Spills	WARNING! EXPLOSIVE. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear full body protective clothing with breathing apparatus. Consider evacuation (or protect in place). In case of transport accident notify Police, Emergency Authority, Competent Explosives Authority or Manufacturer. No smoking, naked lights, heat or ignition sources. Increase ventilation. Use extreme caution to prevent physical shock. Use only spark-free shovels and explosion-proof equipment. Collect recoverable material and segregate from spilled material. Wash spill area with large quantities of water.

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

7.1. Precautions for safe han	dling
Safe handling	 Handle gently. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Avoid all personal contact, including inhalation. Avoid smoking, naked lights, heat or ignition sources. Explosives must not be struck with metal implements. Avoid mechanical and thermal shock and friction. Use in a well ventilated area. Avoid contact with incompatible materials. When handling DO NOT eat, drink or smoke. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately.
Fire and explosion protection	See section 5
Other information	 Store cases in a well ventilated magazine licensed for the appropriate Class, Division and Compatibility Group. Rotate stock to prevent ageing. Use on FIFO (first in-first out) basis. Observe manufacturer's storage and handling recommendations contained within this SDS. Store in a cool place in original containers. Keep containers securely sealed. No smoking, naked lights, heat or ignition sources. Store in an isolated area away from other materials. Keep storage area free of debris, waste and combustibles. Protect containers against physical damage. Check regularly for spills and leaks NOTE: If explosives need to be destroyed contact the Competent Authority. Store away from incompatible materials.

7.2. Conditions for safe storage, including any incompatibilities

Keep out of reach of children.

Suitable container	 All packaging for Class 1 Goods shall be in accordance with the requirements of the relevant Code for the transport of Dangerous Goods. Class 1 is unique in that the type of packaging used frequently has a very decisive effect on the hazard and therefore on the assignment to a particular division
Storage incompatibility	 Avoid contact with other explosives, pyrotechnics, solvents, adhesives, paints, cleaners and unauthorized metals, plastics, packing equipment and materials. Avoid contamination with acids, alkalis, reducing agents, amines and phosphorus. Explosion hazard may follow contact with incompatible materials

7.3. Specific end use(s)

Chemwatch: **65-6265** Version No: **4.1.1.1** Page **5** of **13**

DAY AND NIGHT SIGNAL

Issue Date: 19/09/2016 Print Date: 19/10/2017

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

DERIVED NO EFFECT LEVEL (DNEL)

Not Available

PREDICTED NO EFFECT LEVEL (PNEC)

Not Available

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
European Union (EU) Commission Directive 2006/15/EC establishing a second list of indicative occupational exposure limit values (IOELVs)	barium nitrate	Barium (soluble compounds as Ba)	0,5 mg/m3	Not Available	Not Available	Not Available
EU Consolidated List of Indicative Occupational Exposure Limit Values (IOELVs)	barium nitrate	Barium (soluble compounds as Ba)	0.5 mg/m3	Not Available	Not Available	Not Available
UK Workplace Exposure Limits (WELs)	aluminium	Aluminium metal inhalable dust	10 mg/m3	Not Available	Not Available	Not Available
UK Workplace Exposure Limits (WELs)	aluminium	Aluminium metal respirable dust	4 mg/m3	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
potassium nitrate	Potassium nitrate	9 mg/m3	100 mg/m3	600 mg/m3
magnesium	Magnesium	18 mg/m3	200 mg/m3	1,200 mg/m3
strontium nitrate	Strontium nitrate	5.7 mg/m3	62 mg/m3	370 mg/m3
barium nitrate	Barium nitrate	2.9 mg/m3	350 mg/m3	2,100 mg/m3
potassium perchlorate	Potassium perchlorate	6.3 mg/m3	69 mg/m3	420 mg/m3
sulfur	Sulfur	30 mg/m3	330 mg/m3	2,000 mg/m3
potassium chlorate	Potassium chlorate	5.6 mg/m3	62 mg/m3	370 mg/m3

Ingredient	Original IDLH	Revised IDLH
potassium nitrate	Not Available	Not Available
magnesium	Not Available	Not Available
strontium nitrate	Not Available	Not Available
barium nitrate	50 mg/m3	Not Available
aluminium	Not Available	Not Available
potassium perchlorate	Not Available	Not Available
sulfur	Not Available	Not Available
dihydroxy anthrachinon	Not Available	Not Available
milk sugar	Not Available	Not Available
potassium chlorate	Not Available	Not Available

MATERIAL DATA

8.2. Exposure controls

Engineering controls for explosive articles are designed to reduce or eliminate fragmentation and/or blast effects either by suppression of the source of detonation or by protection at the exposed location, or both. Barricades, shields, contained detonation chambers, and "zero quantity-distance (Q-D)" magazines are examples of engineering controls.

8.2.1. Appropriate engineering controls

Engineering controls are designed and tested in a rigorous fashion. The construction of the engineering control must be carefully duplicated in field applications to assure it will function properly.

It is thus imperative that engineering controls be built exactly in accordance with the design package, and that they be used only for the articles (e.g.munitions) for which they are authorised.

8.2.2. Personal protection







Eye and face protection

- ► Safety glasses with side shields
- Chemical goggles

Skin protection

See Hand protection below

Hands/feet protection


- ► Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber
- Body protection

See Other protection below

Chemwatch: **65-6265**Version No: **4.1.1.1**

Page 6 of 13 DAY AND NIGHT SIGNAL

Issue Date: 19/09/2016 Print Date: 19/10/2017



Respiratory protection

Respiratory protection not normally required due to the physical form of the product.

8.2.3. Environmental exposure controls

See section 12

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Steel tube with orange outer casing pressed with black/grey polytechnical ingredients, contains ignitor and a grip.			
Physical state	Manufactured	Relative density (Water = 1)	Not Applicable	
Odour	Not Available	Partition coefficient n-octanol / water	Not Available	
Odour threshold	Not Available	Auto-ignition temperature (°C)	>160	
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available	
Melting point / freezing point (°C)	Not Applicable	Viscosity (cSt)	Not Applicable	
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable	
Flash point (°C)	160	Taste	Not Available	
Evaporation rate	Not Applicable	Explosive properties	Not Available	
Flammability	Not Applicable	Oxidising properties	Not Available	
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable	
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Applicable	
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available	
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Applicable	
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Applicable	

9.2. Other information

Not Available

SECTION 10 STABILITY AND REACTIVITY

10.1.Reactivity	See section 7.2
10.2. Chemical stability	Presence of shock and friction Presence of heat source and ignition source Product is considered stable under normal handling conditions. Stable under normal storage conditions. Hazardous polymerization will not occur. Avoid contact with other chemicals.
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Inhaled	Not normally a hazard due to physical form of product. Inhalation of vapour is more likely at higher than normal temperatures. The vapour is discomforting
Ingestion	Not normally a hazard due to physical form of product.
Skin Contact	Not normally a hazard due to physical form of product. The vapour is discomforting
Eye	Not normally a hazard due to physical form of product. The vapour is discomforting
Chronic	► Generally not applicable.

Chemwatch: 65-6265 Page 7 of 13 Issue Date: 19/09/2016 Version No: 4.1.1.1

DAY AND NIGHT SIGNAL

TOXICITY IRRITATION DAY AND NIGHT SIGNAL Not Available Not Available TOXICITY IRRITATION dermal (rat) LD50: >5000 $mg/kg^{[1]}$ Not Available potassium nitrate Oral (rat) LD50: >2000 mg/kg^[1] TOXICITY IRRITATION magnesium Oral (rat) LD50: >2000 mg/kg^[1] Not Available TOXICITY IRRITATION strontium nitrate Oral (rat) LD50: 1892 mg/kg^[2] Not Available TOXICITY IRRITATION Oral (rat) LD50: 355 mg/kg^[2] barium nitrate Eye (rabbit):100 mg/24h - moderate Skin (rabbit): 500 mg/24h - mild TOXICITY IRRITATION aluminium Oral (rat) LD50: >2000 mg/kg^[1] Not Available TOXICITY IRRITATION potassium perchlorate Not Available Not Available TOXICITY IRRITATION dermal (rat) LD50: >2000 mg/kg^[1] Eye (human): 8 ppm irritant sulfur Inhalation (rat) LC50: >5.43 mg/l4 h^[1]

Leaend:

potassium chlorate

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

IRRITATION

Not Available

STRONTIUM NITRATE

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

BARIUM NITRATE

The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

ALUMINIUM & POTASSIUM PERCHLORATE

No significant acute toxicological data identified in literature search.

Oral (rat) LD50: >2000 mg/kg^[1]

dermal (rat) LD50: >2000 mg/kg^[1]

Oral (rat) LD50: 1870 mg/kg^[2]

TOXICITY

Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	0	Reproductivity	0
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0

Legend:

★ – Data available but does not fill the criteria for classification

✓ – Data available to make classification

O - Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Print Date: 19/10/2017

Page 8 of 13

Issue Date: 19/09/2016 Print Date: 19/10/2017

DAY AND NIGHT SIGNAL

	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
DAY AND NIGHT SIGNAL	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
potassium nitrate	LC50	96	Fish	22.5mg/L	4
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
	LC50	96	Fish 5		2
magnesium	EC50	72	Algae or other aquatic plants	>20mg/L	2
	NOEC	72	Algae or other aquatic plants	>25.5mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
	LC50	96	Fish	>40.3mg/L	2
strontium nitrate	EC50	72	Algae or other aquatic plants	>43.3mg/L	2
	NOEC	96	Fish	>=40.3mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
	LC50	96	Fish >3.5		2
barium nitrate	EC50	72	Algae or other aquatic plants >1.92		2
	NOEC	72	Algae or other aquatic plants	>=1.92mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
	LC50	96	Fish	0.078-0.108mg/L	2
	EC50	48	Crustacea	0.7364mg/L	2
aluminium	EC50	96	Algae or other aquatic plants	0.0054mg/L	2
	BCF	360	Algae or other aquatic plants 9mg/L		4
	NOEC	72	Algae or other aquatic plants	>=0.004mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
potassium perchlorate	EC10	24	Algae or other aquatic plants	>1000mg/L	4
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
	LC50	96	Fish	<14mg/L	4
sulfur	EC50	48	Crustacea	>5000mg/L	4
	NOEC	504	Crustacea	>0.0025mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
matanakum aklausti	LC50	96	Fish	=13000mg/L	1
potassium chlorate	EC50	72	Algae or other aquatic plants	1.9mg/L	4

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
potassium nitrate	LOW	LOW
sulfur	LOW	LOW
potassium chlorate	HIGH	HIGH

12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
potassium nitrate	LOW (LogKOW = 0.209)
sulfur	LOW (LogKOW = 0.229)
potassium chlorate	LOW (LogKOW = -4.6296)

12.4. Mobility in soil

Ingredient	Mobility
potassium nitrate	LOW (KOC = 14.3)
sulfur	LOW (KOC = 14.3)

DAY AND NIGHT SIGNAL

Issue Date: 19/09/2016 Print Date: 19/10/2017

potassium chlorate

LOW (KOC = 35.04)

12.5.Results of PBT and vPvB assessment

	P	В	Т
Relevant available data	Not Available	Not Available	Not Available
PBT Criteria fulfilled?	Not Available	Not Available	Not Available

12.6. Other adverse effects

No data available

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product / Packaging disposal	 Explosives must not be thrown away, buried, discarded or placed with garbage. Explosives which are surplus, deteriorated or considered unsafe for transport, storage or use shall be destroyed and the statutory authorities shall be notified. This material may be disposed of by burning or detonation but the operation may only be performed under the control of a person trained in the safe destruction of explosives. Refer to local Waste Disposal Authority and supplier for suitable disposal procedure.
Waste treatment options	Not Available
Sewage disposal options	Not Available

SECTION 14 TRANSPORT INFORMATION

Labels Required

	1.4 G 1
Marine Pollutant	NO
HAZCHEM	1YE

Land transport (ADR)

14.1.UN number	0191		
14.2.UN proper shipping name	SIGNAL DEVICES, HAND		
14.3. Transport hazard class(es)	Class 1.4G Subrisk Not Applicable		
14.4.Packing group	Not Applicable		
14.5.Environmental hazard	Not Applicable		
14.6. Special precautions for user	Classification code 1 Hazard Label 1 Special provisions 1	Not Applicable 1.4G Not Applicable 0	

Air transport (ICAO-IATA / DGR)

Air transport (ICAO-IAIA / DGF	()					
14.1. UN number	0191	0191				
14.2. UN proper shipping name	Signal devices, hand	Signal devices, hand				
442 Tarressont barred place(ca)	ICAO/IATA Class	1.4G				
14.3. Transport hazard class(es)		ICAO / IATA Subrisk Not Applicable				
	ERG Code 1L					
14.4. Packing group	Not Applicable					
14.5. Environmental hazard	Not Applicable					
	Special provisions		Not Applicable			
	Cargo Only Packing Instructions		135			
14.6. Special precautions for	Cargo Only Maximum Qty / Pack		75 kg			
user	Passenger and Cargo Packing Instructions		Forbidden			
	Passenger and Cargo Maximum Qty / Pack		Forbidden			
	Passenger and Cargo Limited Quantity Packing Instructions		Forbidden			

Issue Date: 19/09/2016 Print Date: 19/10/2017

DAY AND NIGHT SIGNAL

	Passenger and Cargo Limited Maximum Qty / Pack Forbidden			
Sea transport (IMDG-Code / GO	GVSee)			
14.1. UN number	0191			
14.2. UN proper shipping name	SIGNAL DEVICES, HAND			
14.3. Transport hazard class(es)	IMDG Class 1.4G IMDG Subrisk Not Applicable			
14.4. Packing group	Not Applicable			
14.5. Environmental hazard	Not Applicable			
14.6. Special precautions for user	Special provisions	F-B , S-X Not Applicable 0		
Inland waterways transport (A	DN)			
14.1. UN number	0191			
14.2. UN proper shipping name	SIGNAL DEVICES, HAND			
14.3. Transport hazard class(es)	1.4G Not Applicable			
14.4. Packing group	Not Applicable			
14.5. Environmental hazard	Not Applicable			
14.6. Special precautions for user	Classification code Special provisions Limited quantity Equipment required Fire cones number	1.4G Not Applicable 0 PP		

14.7. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

POTASSIUM NITRATE(7757-79-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

European Customs Inventory of Chemical Substances ECICS (English)

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)

MAGNESIUM(7439-95-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

EU REACH Regulation (EC) No 1907/2006 - Annex XVII - Restrictions on the manufacture. placing on the market and use of certain dangerous substances, mixtures and articles

European Customs Inventory of Chemical Substances ECICS (English)

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)

European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI

STRONTIUM NITRATE(10042-76-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

European Customs Inventory of Chemical Substances ECICS (English)

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)

BARIUM NITRATE(10022-31-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

EU Consolidated List of Indicative Occupational Exposure Limit Values (IOELVs) European Customs Inventory of Chemical Substances ECICS (English)

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)

European Union (EU) Commission Directive 2006/15/EC establishing a second list of indicative occupational exposure limit values (IOELVs) (Spanish)

European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI

UK Workplace Exposure Limits (WELs)

UK Workplace Exposure Limits (WELs)

ALUMINIUM(7429-90-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

EU REACH Regulation (EC) No 1907/2006 - Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles European Customs Inventory of Chemical Substances ECICS (English) European Trade Union Confederation (ETUC) Priority List for REACH Authorisation

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English) European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI

POTASSIUM PERCHLORATE(7778-74-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

European Customs Inventory of Chemical Substances ECICS (English) European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI

SULFUR(7704-34-9.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Page **11** of **13**

Issue Date: 19/09/2016 Print Date: 19/10/2017

DAY AND NIGHT SIGNAL

European Customs Inventory of Chemical Substances ECICS (English)

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)

European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI

POTASSIUM CHLORATE(3811-04-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

European Customs Inventory of Chemical Substances ECICS (English)

Regulation (EU) 2015/830, Regulation (EC) No 1272/2008 and their amendments

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)

European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI

GHS03, Dgr, GHS08

H302, H361, H371, H373

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : 98/24/EC, 92/85/EC, 94/33/EC, 91/689/EEC, 1999/13/EC, Commission

15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

ECHA SUMMARY

Ingredient	CAS number	Index No	ECHA Dossier		
potassium nitrate	7757-79-1	Not Available	01-2119488224-35-XXXX	01-2120104950-66-XXXX	
Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)			Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Ox. Sol. 2, Skin Irrit. 2, Eye Ir	Ox. Sol. 2, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3			H272, H315, H319, H335
2	Ox. Sol. 3, Ox. Sol. 2, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, Ox. Sol. 1, Aquatic Chronic			CHEO2 Day CHEO0	H315, H319, H335, H271, H412,

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

Ingredient	CAS number	Index No	ECHA Dossier
magnesium	7439-95-4	012-001-00-3, 012-002-00-9	01-2119537203-49-XXXX, 01-2119940954-29-XXXX, 01-2120113187-64-XXXX

3, Ox. Liq. 3, Acute Tox. 4, Repr. 2, STOT SE 2, STOT RE 2, Ox. Liq. 2, Ox. Liq. 1

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Pyr. Sol. 1, Water-react. 1	GHS02, Dgr	H250, H260
2	Pyr. Sol. 1, Water-react. 1, Flam. Sol. 1, Self-heat. 1, Water-react. 2, Water-react. 3, Flam. Sol. 2, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, Aquatic Chronic 4, Self-heat. 2	GHS02, Dgr, GHS07	H250, H260, H228, H251, H315, H319, H335, H413
1	Pyr. Sol. 1, Water-react. 1	GHS02, Dgr	H250, H260
2	Pyr. Sol. 1, Water-react. 1, Flam. Sol. 1, Self-heat. 1, Water-react. 2, Water-react. 3, Flam. Sol. 2, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, Aquatic Chronic 4, Self-heat. 2	GHS02, Dgr, GHS07	H250, H260, H228, H251, H315, H319, H335, H413

 $Harmonisation \ \ Code\ 1 = The\ most\ prevalent\ classification.\ Harmonisation\ \ Code\ 2 = The\ most\ severe\ classification.$

Ingredient	CAS number	Index No	ECHA Dossier
strontium nitrate	10042-76-9	Not Available	01-2119615605-42-XXXX, 01-2120105844-60-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Ox. Sol. 1, Eye Dam. 1	GHS03, GHS05, Dgr	H271, H318
2	Ox. Sol. 1, Eye Dam. 1, Ox. Sol. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, Ox. Sol. 2, Ox. Liq. 3	GHS03, GHS05, Dgr, GHS02	H271, H318, H302, H315, H335

 $Harmonisation\ Code\ 1 = The\ most\ prevalent\ classification.\ Harmonisation\ Code\ 2 = The\ most\ severe\ classification.$

Ingredient	CAS number	Index No	ECHA Dossier
barium nitrate	10022-31-8	056-002-00-7	01-2119986880-22-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Ox. Sol. 2, Acute Tox. 4	GHS03, GHS07, Dgr	H272, H302, H332
2	Ox. Sol. 2, Acute Tox. 3, Eye Irrit. 2, Acute Tox. 4, Ox. Liq. 2	GHS03, GHS06, Dgr	H272, H301, H319, H332, H312

 $Harmonisation \ \ Code\ 1 = The\ most\ prevalent\ classification.\ Harmonisation\ \ Code\ 2 = The\ most\ severe\ classification.$

Ingredient	CAS number	Index No	ECHA Dossier
aluminium	7429-90-5	013-001-00-6, 013-002-00-1	01-2119529243-45-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Flam. Sol. 1, Water-react. 2	GHS02, Dgr	H228, H261
2	Flam. Sol. 1, Water-react. 2, Pyr. Sol. 1, Acute Tox. 3, Flam. Sol. 2, Aquatic Chronic 4, STOT RE 2, Aquatic Acute 1, Pyr. Liq. 1, STOT RE 1, Skin Sens. 1, Water-react. 1	Dgr, GHS01, GHS09, GHS05, GHS06, GHS08	H228, H261, H250, H413, H302, H311, H315, H331, H400, H372, H317
1	Flam. Sol. 1, Water-react. 2	GHS02, Dgr	H228, H261
2	Flam. Sol. 1, Water-react. 2, Pyr. Sol. 1, Acute Tox. 3, Flam. Sol. 2, Aquatic Chronic 4, STOT RE 2, Aquatic Acute 1, Pyr. Liq. 1, STOT RE 1, Skin Sens. 1, Water-react. 1	Dgr, GHS01, GHS09, GHS05, GHS06, GHS08	H228, H261, H250, H413, H302, H311, H315, H331, H400, H372, H317
1	Skin Irrit. 2, Eye Irrit. 2, Aquatic Acute 1, Aquatic Chronic 2	GHS09, GHS07, Wng	H315, H319, H400, H411

Page **12** of **13**

Issue Date: 19/09/2016 Print Date: 19/10/2017

DAY AND NIGHT SIGNAL

2	Skin Irrit. 2, Eye Irrit. 2, Aquatic Acute 1, Aquatic Chronic 2	GHS09, GHS07, Wng	H315, H319, H400, H411
1	Not Classified	Not Available	Not Available
2	Not Classified	Not Available	Not Available

 $Harmonisation \ \ Code\ 1 = The\ most\ prevalent\ classification.\ Harmonisation\ \ Code\ 2 = The\ most\ severe\ classification.$

Ingredient	CAS number	Index No	ECHA Dossier
potassium perchlorate	7778-74-7	017-008-00-5	01-2120021000-89-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Ox. Sol. 1, Acute Tox. 4	GHS03, GHS07, Dgr	H271, H302
2	Ox. Sol. 1, Acute Tox. 4, Ox. Liq. 1, Eye Irrit. 2, STOT RE 2	GHS03, Dgr, GHS08	H271, H302, H319, H373

 $Harmonisation\ Code\ 1 = The\ most\ prevalent\ classification.\ Harmonisation\ Code\ 2 = The\ most\ severe\ classification.$

Ingredient	CAS number	Index No	ECHA Dossier
sulfur	7704-34-9.	016-094-00-1	01-2119487295-27-XXXX, 01-2119422098-42-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Skin Irrit. 2	GHS07, Wng	H315
2	Skin Irrit. 2, Self-react. C, Acute Tox. 4, Aquatic Chronic 3, Flam. Sol. 2, Eye Irrit. 2, STOT SE 3, Flam. Sol. 1	GHS07, GHS02, Dgr	H242, H302, H332, H412, H228, H319, H335, H314

 $Harmonisation \ \ Code\ 1 = The\ most\ prevalent\ classification.\ Harmonisation\ \ Code\ 2 = The\ most\ severe\ classification.$

Ingredient	CAS number	Index No	ECHA Dossier
potassium chlorate	3811-04-9	017-004-00-3	01-2119494917-18-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Ox. Sol. 1, Acute Tox. 4, Aquatic Chronic 2	GHS09, GHS03, GHS07, Dgr	H271, H302, H332, H411
2	Ox. Sol. 1, Acute Tox. 4, Aquatic Chronic 2, Ox. Sol. 2, STOT SE 2, Aquatic Chronic 3	GHS09, GHS03, GHS07, Dgr	H271, H302, H332, H411, H371

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

National Inventory	Status	
Australia - AICS	Υ	
Canada - DSL	Υ	
Canada - NDSL	N (strontium nitrate; sulfur; barium nitrate; magnesium; aluminium; potassium chlorate; potassium perchlorate; potassium nitrate)	
China - IECSC	Υ	
Europe - EINEC / ELINCS / NLP	Υ	
Japan - ENCS	N (sulfur; magnesium; aluminium)	
Korea - KECI	Υ	
New Zealand - NZIoC	Υ	
Philippines - PICCS	Υ	
USA - TSCA	Υ	
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)	

SECTION 16 OTHER INFORMATION

Full text Risk and Hazard codes

H228	Flammable solid.
H242	Heating may cause a fire.
H250	Catches fire spontaneously if exposed to air.
H251	Self-heating: may catch fire.
H260	In contact with water releases flammable gases which may ignite spontaneously.
H261	In contact with water releases flammable gases.
H271	May cause fire or explosion; strong oxidiser.
H272	May intensify fire; oxidiser.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.

Chemwatch: 65-6265 Version No: 4.1.1.1

Page 13 of 13 DAY AND NIGHT SIGNAL

Issue Date: 19/09/2016 Print Date: 19/10/2017

H317	May so use an ellegale dela recetion	
пэт	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H331	Toxic if inhaled.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H361	Suspected of damaging fertility or the unborn child.	
H371	May cause damage to organs.	
H372	Causes damage to organs through prolonged or repeated exposure.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
H413	May cause long lasting harmful effects to aquatic life.	

Other information

Ingredients with multiple cas numbers

Name	CAS No
strontium nitrate	10042-76-9, 13470-05-8
barium nitrate	10022-31-8, 34053-87-7
aluminium	7429-90-5, 91728-14-2

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit.

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL: No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index